

Open Frame LCD

Open Frame High Brightness Display




5.7" (4:3)

Specifications

RoHS
COMPLIANT
2011/65/EU

Model Name	R05T100-OFD1HB
Panel Size	5.7"
Active Display Area(mm)	115.2 (H) x 86.4 (V)
Resolution	640 x 480
Brightness(cd/m2)	900 (Typical)
Contrast Ratio	300:1 (Typical)
Viewing Angles(CR>=10 L/R/U/D)	-70~70(H) ; -40~60(V)
Display Colors	262K (6 bits/color)
Standard Input Signal	1 x VGA (D-sub 15) 1 x HDMI (Type-A)
Touch Screen(Optional-1)	Resistive Touch Protective Glass
Touch Interface	USB / RS232
Audio / Speakers (Optional)*	Audio line in (3.5mm) + Speaker x2
OSD	5 Keys: -, +, Power, Esc, Enter
Power Input	12V DC input (2.5ψ) with external AC-DC Adapter (100V~240V)
Power Consumption	15W typical, Normal operation
Operating temperature	0~50°C
Storage Temperature	-10~60°C
Accessories	Power AC-DC Adapter(100V~240V) VGA cable (1.8m) HDMI cable (2m)




1. VGA
2. HDMI
3. DC input

I/O Optional

Optional 1*	1 x VGA (D-sub 15) 1 x S-Video 1 x Composite
-------------	--

*Outside dimension and I/O will be different from standard

Mechanical Drawing



UNIT:mm

* Note: The mechanical drawing may change when adding touch screen. Please contact our sales representative if you need further product information.