M101P-ME, 10.1-inch Rugged Tablet PC

A Tablet Computer for Healthcare Professionals that Saves Time and Improves Efficiency

M101P-ME is a medically certified Windows-based tablet computer with a housing enhanced with antimicrobial properties, weighting at just 1200 grams (2.7 pounds). This mobile and portable device is flexible enough to function as a standalone device and competent enough to be used for all sorts of data collection, patient care, information management and wireless communication in medical environments.

With rugged features, a crystal clear 1920 x 1200 resolution display, projected capacitive touch screen, barcode scanner and superior processing power coming from Intel's Apollo Lake processor, this tablet can be used in hospital halls, waiting rooms or nurse stations for communicating and documenting patient information, allowing paramedics and nurses to instantly access and keep patient records.



Highlights

- 10.1" 1920 x 1200 IPS LED Panel with direct optical bonding
- Intel® Apollo Lake Pentium N4200 processor
- Housing enhanced with antimicrobial properties
- Long battery life
- USB3.0 (Type C) connector
- Optional 1D/2D barcode scanner to scan medications or wrist bands
- Lightweight, rugged, IP65 waterproof and dustproof
- IEC 60601-1, 60601-1-2 Medically Certified

Order Information				
	3G	4G	1D/2D Barcode Reader	HF RFID
M101P-ME	Optional	Optional	N/A	N/A
M101P-MEHF	Optional	Optional	N/A	Default
M101P-MEBH	Optional	Optional	Default	N/A
M101P-MEH2	Optional	Optional	Default	Default

M101P-ME 10.1-inch Rugged Tablet PC

A Tablet Computer for Healthcare Professionals that Saves Time and Improves Efficiency

Weight

Housing

Humidity

IP Proof

Vibration

Power Input

Battery

Shock

Drop

Storage Temperature

Power Management

Mechanical and Environment

Operating Temperature 0°C to 35°C (32°F to 95°F)

12-19V DC

Dimension (W x L x H) 271.8 x 197.2 x 19 mm (10.7 x 7.76 x 0.75 inches) 4

-30°C to 70°C (-22°F to 158°F)

10% to 90% RH, non-condensing

IP65 certified, Dustproof and waterproof

MIL-STD-810G Method 516.6 Procedure I

MIL-STD-810G Method 514.6 Procedure I MIL-STD-810G Method 516.6, 4 ft to concrete

7.4V, typ. 5140 mAh Li-Polymer Battery (2S1P)

7.4V, typ. 10280 mAh Li-Polymer Battery (2S2P, optional)

1.2 kg (2.7 lbs) with standard battery,

1.4 kg (3.1 lbs) with optional high capacity battery

Rugged housing enhanced with antimicrobial properties

Display Specification	
Size	10.1-inch IPS display with LED Backlight
Resolution Brightness	1920 x 1200 WUXGA 600 nit
Touch	With direct optical bonding for sunlight readable Multi-touch projected capacitive
Contrast Ratio	800:1
Viewing Angle Technology	85/85/85 • Ant- reflective and anti-glare technology (Optional)
reennology	 Ambient light sensor, e-compass, gyro, acceleration
	sensors Automatic screen rotation
	• Intel HD Graphics (built-in CPU) video controller
System Specification	
Processor	Intel Pentium N4200 Processor
System Memory	1.10 GHz, up to 2.50 GHz with turbo boost technology 4GB SODIMM DDR3L-1600 (up to 8GB) ¹
Storage	64GB solid state drive (SSD)
	Optional up to 512GB, up to 128GB additional storage with optional microSDXC card slot
Operating System	Windows 10 IoT Enterprise (64 bit)
Wireless Communicati	on
WLAN	802.11 a/b/g/n/ac
Bluetooth GNSS	Bluetooth 4.2 GPS, GLONASS, BeiDou
WWAN	 Optional 4G (LTE, HSPA+, GSM/GPRS/EDGE, EV-DO
	Rev A, 1xRTT) • Optional 3G (HSPA+, GSM/GPRS/EDGE)
Interface	
Docking Connector	1 x 19-pin docking connector
HDMI USB	1 x Optional micro HDMI 1 x USB3.0 (Type A), 1 x USB3.0 (Type C)
Power Input Micro SD	1 x Power Jack
Audio Connector	1 x Micro SD Slot 1 x Audio Combo connector (Mic in or Line Out)
Keyboard and Input	
Touch	 10-point multi touch, support Rain, Glove, Stylus
Button	On-screen QWERTY keyboard Button 1 x power, 1 x Home, 2 x volume key,
	2 x function key (Programmable
LED Indicators	function key configured by Hottab Utility) Power, Battery, HDD, RF
Audio	
Microphone	Built-in dual Digital Mic with Noise Cancellation
Speaker	2 x 1 watt speaker
Cameras	
Web Camera	2MP webcam
Rear Camera	8MP rear camera with autofocus and LED light
Data Capture	
Barcode HF RFID	Optional 1D/2D Barcode Reader Optional HF RFID reader 13.56 MHz
Security Function	
Security	 Password security for user and hard disk lock
Mobile Device Mgmt.	Trusted Platform Module (TPM) 2.0 ² SOTI Mobicontrol compatible ³
Regulatory Approvals	

Regulatory Approvals

Certificate

• CE, FCC, IC • IEC 60601-1, IEC 60601-1-2,

EN 60601-1, ANSI/AAMI ES 60601-1

Battery Operating Time Std. Battery: 8 hours 6 High Capacity Battery: 16 hours 100-240V, 50-60Hz / 19V DC Adapter Accessories Standard Accessories Adapter and Power Cord 922D065W19V1 Standard Battery 98K000A00095 9B000000415 Capacitive Stylus **Optional Accessories** 98DT00A0000G Desk Dock 98K000A0003L Vehicle Dock (without VGA output) Battery Charger 98KT00A0000F Active Pen 98K000A0007D Smart Card Reader 98K000A0003U 98K000A0003J Hand Strap UHF RFID Reader 98K000A0004J VESA Mount Kit 98K000A0003O Shoulder Strap 98K000A0003Q 9B00000003J Carry Bag Micro HDMI Cable 9491191190K1 Vehicle Charger 9226065W19V0 9B00000007B Mobile Printer MX20 Mobile Printer MX30 9B00000007A







Do Not Expose the Battery Pack to Excessive Heat, or Extreme Heat (Near Fire, in Direct Sunlight for example)

Do not expose bare skin to this product when handling this unit in extreme hot or cold environments

- 1. Total usable memory will be less depending upon actual system configuration.
- TPM 2.0 available upon request.
- 3. SOTI is available upon request.
- 4. Length measurements do not include protrusions. Weight varies with options and active pen.
- 5. The drop test with high-capacity battery must come with hand strap.
- 6. Measured at dimming LCD brightness. Varies depending on the usage conditions, or when an external device is attached."
- 7. Accessories and Integrated Options may vary depending on your configuration.
- 8. This is a simplified drawing and some components are not marked in detail.