


12.1" GC65 Panel PC (Standard I/O) -R12FA3S-GCM2(HB)

Features

- 12.1" 1024 x 768 with P-CAP touchscreen
- Low power consumption with Freescale® Cortex® A9
- Fanless cooling system and ultra low power consumption
- Front IP65 for protection against water and dust
- A true flat, easy-to-clean front surface with edge-to-edge design
- Plenty of I/O, including 1 x LAN, 1 x RS232, 1 x USB 2.0, 1 x USB OTG, 1 x CANbus



Specifications

System

- Processor : Freescale Cortex A9 i.MX6 Dual Core GHz
- System Memory : 1GB LPDDR3
- Storage : Onboard 16GB eMMC(default) /Micro SD card

Input / Output

- Serial Ports : 1 x RS-232/422/485, 1 x CANbus
- USB Ports : 1 x USB 2.0, 1 x USB OTG
- Ethernet : 1 x RJ 45-10/100/1000 Mbps (LAN)
- Speaker : 1 x 2 Watt Speaker
- SD Card : 1 x Micro SD Card Reader

Environment

- Operating Temperature : -15 °C to 55 °C
- Operating Humidity : 10% to 95% (non-condensing)
- IP Rating : Front IP65
- Shock Operating : 40g for 11ms
- Vibration Operating : 1.48/1.98/2.24 g rms for XYZ/ 5-500Hz

Power Considerations

- Power Input : 12V DC in

Display

- Size/Type : 12.1" TFT (widescreen)
- Resolution : 1024 x 768
- Brightness : 700 cd/m (typ.)
- Contrast Ratio : 500:1 (typ.)
- Viewing Angle : -80~80 (H); -70~70 (V)
- Max Colors : 16.2M
- Active Display Area : 245.76 (H) x 184.32 (V)

Mechanical Specification

- Cooling System : Fanless design
- Mounting : VESA Mount (75x75mm), Panel Mount
- Dimensions (W x H xD) : 296.2 x 226.7 x 45.5 (mm)

Operating System

- Android 6.0 (Default)

