


ICO100-839

NEW

Robust DIN-rail Fanless Embedded System with Intel® Celeron® Processor N3350, 2 COM, LAN, 2 USB and DIO

Features


- Extreme cost-effective with fanless and cableless design
- Intel® Celeron® processor N3350 (1.1 GHz)
- 2 COM, 2 USB and GbE LAN
- 8-bit programmable DIO for IoT gateway applications
- Wide operating temperature range from -40°C to +70°C
- 12 ~ 24 VDC wide range power input
- OVP, UVP, OCP, RPP power protection design
- AXView 2.0 intelligent embedded monitoring software for IIoT




▲ Front view



▲ Rear view



USB Power DC-In



VGA DIO



Specifications

Standard Color	Extruded aluminum and heavy-duty steel, IP40	
Construction	Aluminum, IP40	
CPU	Intel® Celeron® processor N3350 (1.1 GHz, Dual Core)	
System Board	SBC87839	
System Memory	1 x DDR3L-1866 SO-DIMM, up to 8GB	
BIOS	AMI UEFI BIOS	
System I/O Outlet	Serial Port	2 x RS-232/422/485 (COM 1-2) Interface select by BIOS Supports Auto Flow Control in RS-485 mode
	RTC	Battery onboard
	USB	2 x USB 2.0
	Storage	mSATA shared with mPCIe slot (option eMMC flash onboard)
	LAN	1 x 10/100/1000 Mbps Ethernet (Intel® i211AT for ICO100) (Intel® i210IT for ICO100-WT) Magnetic isolation protection 1.5KV
	VGA	1 x DB15 connector
	DIO	1 x DI/DO (8-bit programmable, DB9 female connector) Voltage is 5V TTL-level Programming: I/O sink current is 10mA (max.) Input/output can be programming
	Power Input	1 x DC power input with terminal block

Extension	1 x full-size PCI Express Mini Card slot with SIM slot (For wireless module) 1 x full-size PCI Express Mini Card slot (For wireless module or mSATA)
Watchdog Timer	1 WDT One step is 1 sec. 255 levels
System Indicator	Power, Active
Power Supply	Power Input Range: 12 ~ 24 VDC, 1.15 ~ 0.62A (13.80W~ 14.88W) Protection: OVP (±20%), reverse protection
Operating Temperature	-20°C ~ +70°C (-4°F ~ +158°F) -40°C ~ +70°C (-40°F ~ +158°F) (ICO100-WT)
Humidity	10% ~ 95%
Vibration Endurance	2 Gms (5 ~ 500Hz, amplitude 0.35 mm; operation/storage/transport)
Weight (net/gross)	0.3 kg (0.67 lb)/0.46 kg (1 lb)
Certificate	CE FCC Class A
Dimensions	31 mm (1.22") (W) x 100 mm (3.93") (D) x 125 mm (4.92") (H)
EOS Support	Windows® 10 IoT Linux support package(By Request) AXView 2.0

Ordering Information

Standard	
IC0100-839-N3350-DC (P/N: E22C100104)	Robust DIN-rail fanless embedded system with Intel® Celeron® processor N3350, 2 COM, LAN, 2 USB and DIO (-20°C to +70°C)
IC0100-839-N3350-WT-DC (P/N: E22C100105)	Robust DIN-rail fanless embedded system with Intel® Celeron® processor N3350, 2 COM, LAN, 2 USB and DIO (-40°C to +70°C)

Optional	
mSATA	
Wall mount kit	
8812C1003A0E	IC0100/IC0120 wall mount bracket kit SFP
PCI Express Mini Card slot: Wi-Fi/3G/4G	
8816N3234A0E	3G/GPS UC20G kit for tBOX (3G ANT) (E)
8816N3235A0E	3G/GPS UC20G kit for tBOX (3G/GPS ANT) (E)
8812C3003A0E	SparkLAN WPEA-152GN Wi-Fi kit ICO SFP (E)
8812C3004A0E	SparkLAN WPEA-251N Wi-Fi kit ICO SFP (E)
822C3001060E	LTE SIMCOM SIM7100C (TW) for ICO300 SFP

* Specification and certifications are based on requirements and may vary.

Dimensions

