Open Frame LCD

(LED Backlight)

32"(16:9)

Specifications

RoHS COMPLIANT 2011/65/EU

Model Name	W32L100-POA3
Panel Size	32"
Active Dipsplay Area(mm)	698.4 (H) x 392.85 (V)
Resolution	1920 x 1080
Brightness(cd/m2)	350 (Typical)
Contrast Ratio	3000:1 (Typical)
Viewing Angles(CR>=10 L/R/U/D)	-89~89(H) ; -89~89(V)
Display Colors	16.7M (8 bits/color)
Standard Input Signal	1 x VGA (D-sub 15) 1 x HDMI (Type-A)
Touch Screen	Projected Capacitive
Touch Interface	USB
Audio / Speakers (Optional)*	Audio line in (3.5mm) + Speaker x 2
OSD	5 Keys: - , + , Power , Esc , Enter
Power Input	24V DC input (2.5ψ) with external AC-DC Adapter (100V~240V)
Power Consumption	75W typical , Normal operation
Operating tempurature	0~50ºC
Storage Tempurature	-10~60ºC
Accessories	Power AC-DC Adapter(100V~240V) VGA cable (1.8m) HDMI cable (2m)

*Outside dimension and I/O will be different from standard



1. Touch
2. VGA
3. HDMI
4. DC input

I/O Optional	
Optional 1*	1 x VGA (D-sub 15) 1 x HDMI (Type-A) 1 x DVI-D
Optional 2*	1 x VGA (D-sub 15) 1 x DVI-D 1 x S-Video 1 x Composite

Mechanical Drawing



UNIT:mm

* Note: this is a simplified drawing and some components are not marked in detail.
Please contact our sales representative if you need further product information.